

CONDITIONS TO AVOID
ELEVATED TEMPERATURES

SOURCES OF IGNITION

INCOMPATIBILITY (MATERIALS TO AVOID)
STRONG ACIDS AND STRONG OXIDIZING AGENTS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

THERMAL DECOMPOSITION OR COMBUSTION CAN PRODUCE FUMES CONTAINING ORGANIC ACIDS, CARBON DIOXIDE AND CARBON MONOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

HIGH VAPOR/AEROSOL CONCENTRATIONS (GREATER THAN APPROXIMATELY 1000 PPM) ARE IRRITATING TO THE EYES AND THE RESPIRATORY TRACT, MAY CAUSE HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS, AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS, INCLUDING DEATH.

EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MAY CAUSE EYE IRRITATION. DIRECT CONTACT MAY CAUSE STINGING, TEARING AND REDNESS.

SKIN CONTACT AND ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

WARNING AVOID ALL CONTACT WITH SKIN. PENETRATES SKIN READILY. ANY CONTACT MAY RESULT IN THE ABSORPTION OF POTENTIALLY HARMFUL AMOUNTS WHICH CAN CAUSE DAMAGE TO THE KIDNEYS, LIVER, BLOOD AND/OR BONE MARROW.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

MODERATELY TOXIC. MAY CAUSE MOUTH, THROAT, ESOPHAGUS AND STOMACH IRRITATION, NAUSEA, VOMITING AND DIARRHEA. ASPIRATION OF MATERIAL INTO LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

HEALTH HAZARDS

INFORMATION NOT AVAILABLE

CARCINOGENICITY: NTP CARCINOGEN: NO IARC MONOGRAPHS: NO OSHA REGULATED:
NO

INFORMATION NOT AVAILABLE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

OVEREXPOSURE TO VAPOR, DUST OR MIST MAY AGGRAVATE EXISTING RESPIRATORY CONDITIONS, SUCH AS ASTHMA, BRONCHITIS, AND INFLAMMATORY OR FIBROTIC RESPIRATORY DISEASE.

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH IMMEDIATELY WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES. IF IRRITATION PERSISTS, GET MEDICAL ATTENTION.

SKIN CONTACT: WASH CONTAMINATED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS.

INHALATION OF VAPORS OR SPRAY MIST: REMOVE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION IF BREATHING HAS STOPPED.

INGESTION: GET MEDICAL HELP IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, AND ELECTRICAL, STATIC, OR FRICTIONAL SPARKS). AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN AND REMOVE WITH VERMICULITE OR OTHER INERT MATERIAL. PLACE IN A CONTAINER FOR CHEMICAL WASTE. IF LARGE SPILL, FLUSH SPILL AREA WITH WATER SPRAY AND PREVENT RUNOFF FROM ENTERING DRAINS, SEWERS, OR STREAMS.

WASTE DISPOSAL METHOD

DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. INCINERATE IN APPROVED FACILITY.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

DO NOT STORE ABOVE 120 DEG.F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP AWAY FROM HEAT, SPARKS AND FLAME. KEEP CONTAINERS CLOSED WHEN NOT IN USE AND UPRIGHT TO PREVENT LEAKAGE.

OTHER PRECAUTIONS

AVOID CONTACT WITH SKIN OR EYES. WASH THOROUGHLY AFTER HANDLING.

HOT ORGANIC CHEMICAL VAPORS OR MISTS ARE SUSCEPTIBLE TO SUDDEN SPONTANEOUS COMBUSTION WHEN MIXED WITH AIR. IGNITION MAY OCCUR AT TEMPERATURES BELOW THOSE PUBLISHED IN THE LITERATURE AS "AUTOIGNITION" OR "IGNITION" TEMPERATURES. IGNITION TEMPERATURES DECREASE WITH INCREASING VAPOR VOLUME AND VAPOR/AIR CONTACT TIME, AND ARE INFLUENCED BY PRESSURE CHANGES.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

DO NOT BREATHE VAPORS. WHEN CONCENTRATIONS EXCEED THE ESTABLISHED EXPOSURE LIMITS, WEAR AN APPROPRIATE, PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED) UNTIL VAPORS ARE EXHAUSTED. FOLLOW RESPIRATOR MANUFACTURER'S DIRECTIONS FOR RESPIRATOR USE. OBSERVE OSHA STANDARD 29CFR 1910.134.

VENTILATION

PROVIDE GENERAL CLEAN AIR DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP THE AIR CONTAMINANT CONCENTRATION BELOW THE LOWER EXPLOSION LIMIT AND BELOW CURRENT APPLICABLE EXPOSURE LIMITS. REFER TO OSHA STANDARD 1910.94.

PROTECTIVE GLOVES

USE SOLVENT IMPERMEABLE GLOVES TO AVOID CONTACT WITH PRODUCT.

EYE PROTECTION

DO NOT GET IN EYES. USE SAFETY EYEWEAR WITH SPLASH GUARDS OR SIDE SHIELDS, CHEMICAL GOGGLES, FACE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

AVOID CONTACT WITH SKIN. USE PROTECTIVE CLOTHING. PREVENT CONTACT WITH CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING, INCLUDING SHOES, BEFORE REUSE.

WORK/HYGIENIC PRACTICES

WASH AT THE END OF EACH WORKSHIFT AND BEFORE EATING, SMOKING, OR USING THE TOILET. USE APPROPRIATE HAND AND SKIN LOTIONS TO PROTECT THE SKIN.

===== SECTION IX - DISCLAIMER =====

THIS DOCUMENT HAS BEEN PREPARED USING DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE. IT DOES NOT CONSTITUTE A WARRANTY, EXPRESS OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN. ACTUAL CONDITIONS OF USE AND HANDLING ARE BEYOND SELLER'S CONTROL. USER IS RESPONSIBLE TO EVALUATE ALL AVAILABLE INFORMATION WHEN USING PRODUCT FOR ANY PARTICULAR USE AND TO COMPLY WITH ALL FEDERAL, STATE, PROVINCIAL AND LOCAL LAWS AND REGULATIONS.

The following boilerplate keys do not have matching boilerplate key prefixes in the MSDS Master Format file:

- CW01
- EG01
- EY01
- FH01
- FI01
- OD01
- RC01
- RO01
- RU01
- SG01
- SG02
- SK01
- SL01
- TX01
